



Figure similar

Article No. : 1FK7042-2AC71-1BG0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

| | |
|-----------------------|-------------------------|
| Rated speed (100 K) | 2,000 rpm |
| Number of poles | 8 |
| Rated torque (100 K) | 2.8 Nm |
| Rated current | 1.6 A |
| Static torque (60 K) | 2.50 Nm |
| Static torque (100 K) | 3.00 Nm |
| Stall current (60 K) | 1.30 A |
| Stall current (100 K) | 1.61 A |
| Moment of inertia | 2.900 kgcm ² |
| Efficiency | 88.0 % |

Physical constants

| | |
|-----------------------------|--------------------------------|
| Torque constant | 1.86 Nm/A |
| Voltage constant at 20° C | 122.0 V/1000*min ⁻¹ |
| Winding resistance at 20° C | 8.60 Ω |
| Rotating field inductance | 64.0 mH |
| Electrical time constant | 7.40 ms |
| Mechanical time constant | 2.15 ms |
| Thermal time constant | 30 min |
| Shaft torsional stiffness | 15,500 Nm/rad |
| Net weight of the motor | 4.6 kg |

Mechanical data

| | |
|--------------------------|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | Compact |
| Shaft height | 48 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.040 mm |
| Concentricity tolerance | 0.08 mm |
| Axial runout tolerance | 0.08 mm |
| Vibration severity grade | Grade A |
| Connector size | 1 |
| Degree of protection | IP64 |
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Temperature monitoring | Pt1000 temperature sensor |
| Electrical connectors | Connectors for signals and power rotatable |
| Color of the housing | Standard (Anthracite RAL 7016) |
| Holding brake | without holding brake |
| Shaft end | Plain shaft |
| Encoder system | Encoder AS24DQI: absolute encoder single-turn 24 bits |

Optimum operating point

| | |
|---------------|-----------|
| Optimum speed | 2,000 rpm |
| Optimum power | 0.6 kW |

Limiting data

| | |
|-----------------------------------|-----------|
| Max. permissible speed (mech.) | 9,000 rpm |
| Max. permissible speed (inverter) | 4,750 rpm |
| Maximum torque | 10.5 Nm |
| Maximum current | 5.6 A |

Recommended Motor Module

| | |
|--------------------------|----------|
| Rated inverter current | 3 A |
| Maximum inverter current | 9 A |
| Maximum torque | 10.50 Nm |