



Figure similar

Article No. : 1FK7080-2AF71-1CG2

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

|                       |                          |
|-----------------------|--------------------------|
| Rated speed (100 K)   | 3,000 rpm                |
| Number of poles       | 8                        |
| Rated torque (100 K)  | 6.8 Nm                   |
| Rated current         | 4.4 A                    |
| Static torque (60 K)  | 6.60 Nm                  |
| Static torque (100 K) | 8.00 Nm                  |
| Stall current (60 K)  | 4.00 A                   |
| Stall current (100 K) | 4.90 A                   |
| Moment of inertia     | 14.200 kgcm <sup>2</sup> |
| Efficiency            | 92.0 %                   |

### Physical constants

|                             |                                |
|-----------------------------|--------------------------------|
| Torque constant             | 1.61 Nm/A                      |
| Voltage constant at 20° C   | 105.0 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 0.98 Ω                         |
| Rotating field inductance   | 17.2 mH                        |
| Electrical time constant    | 17.50 ms                       |
| Mechanical time constant    | 1.52 ms                        |
| Thermal time constant       | 40 min                         |
| Shaft torsional stiffness   | 120,000 Nm/rad                 |
| Net weight of the motor     | 10.3 kg                        |

### Mechanical data

|                          |   |
|--------------------------|---|
| Motor type               | Permanent-magnet synchronous motor  |
| Motor type               | Compact   |
| Shaft height             | 80  |
| Cooling                  | Natural cooling   |
| Radial runout tolerance  | 0.050 mm  |
| Concentricity tolerance  | 0.10 mm   |
| Axial runout tolerance   | 0.10 mm   |
| Vibration severity grade | Grade A   |
| Connector size           | 1   |
| Degree of protection     | IP65 and DE flange IP67   |
| Design acc. to Code I    | IM B5 (IM V1, IM V3)  |
| Temperature monitoring   | Pt1000 temperature sensor   |
| Electrical connectors    | Connectors for signals and power rotatable  |
| Color of the housing     | Standard (Anthracite RAL 7016)  |
| Holding brake            | without holding brake   |
| Shaft end                | Plain shaft   |
| Encoder system           | Encoder AM24DQI: absolute encoder 24 bits (resolution 16777216, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions) |

### Optimum operating point

|               |           |
|---------------|-----------|
| Optimum speed | 3,000 rpm |
| Optimum power | 2.1 kW    |

### Limiting data

|                                   |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 6,000 rpm |
| Max. permissible speed (inverter) | 5,500 rpm |
| Maximum torque                    | 25.0 Nm   |
| Maximum current                   | 18.0 A    |

### Recommended Motor Module

|                          |          |
|--------------------------|----------|
| Rated inverter current   | 5 A      |
| Maximum inverter current | 15 A     |
| Maximum torque           | 22.10 Nm |