



Figure similar

Article No. : 1FK7105-2AC71-1UH0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

|                       |                           |
|-----------------------|---------------------------|
| Rated speed (100 K)   | 2,000 rpm                 |
| Number of poles       | 8                         |
| Rated torque (100 K)  | 37.0 Nm                   |
| Rated current         | 16.0 A                    |
| Static torque (60 K)  | 40.00 Nm                  |
| Static torque (100 K) | 48.00 Nm                  |
| Stall current (60 K)  | 16.20 A                   |
| Stall current (100 K) | 20.00 A                   |
| Moment of inertia     | 162.000 kgcm <sup>2</sup> |
| Efficiency            | 93.0 %                    |

### Physical constants

|                             |                                |
|-----------------------------|--------------------------------|
| Torque constant             | 2.37 Nm/A                      |
| Voltage constant at 20° C   | 157.5 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 0.17 Ω                         |
| Rotating field inductance   | 4.5 mH                         |
| Electrical time constant    | 25.50 ms                       |
| Mechanical time constant    | 1.40 ms                        |
| Thermal time constant       | 70 min                         |
| Shaft torsional stiffness   | 95,000 Nm/rad                  |
| Net weight of the motor     | 43.5 kg                        |

### Mechanical data

|                          |  |
|--------------------------|--|
| Motor type               | Permanent-magnet synchronous motor                                       |
| Motor type               | Compact  |
| Shaft height             | 100  |
| Cooling                  | Natural cooling  |
| Radial runout tolerance  | 0.050 mm   |
| Concentricity tolerance  | 0.10 mm  |
| Axial runout tolerance   | 0.10 mm  |
| Vibration severity grade | Grade A  |
| Connector size           | 1.5  |
| Degree of protection     | IP64   |
| Design acc. to Code I    | IM B5 (IM V1, IM V3)   |
| Temperature monitoring   | Pt1000 temperature sensor  |
| Electrical connectors    | Connectors for signals and power rotatable                               |
| Color of the housing     | Standard (Anthracite RAL 7016)   |
| Holding brake            | with holding brake   |
| Shaft end                | Plain shaft  |
| Encoder system           | Resolver R15DQ: resolver 15 bits (resolution 32768, internal multi-pole) |

### Optimum operating point

|               |           |
|---------------|-----------|
| Optimum speed | 2,000 rpm |
| Optimum power | 7.7 kW    |

### Limiting data

|                                   |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 5,000 rpm |
| Max. permissible speed (inverter) | 3,650 rpm |
| Maximum torque                    | 150.0 Nm  |
| Maximum current                   | 71.0 A    |

### Holding brake

|                       |                        |
|-----------------------|------------------------|
| Holding brake version | Permanent-magnet brake |
| Holding torque        | 43.0 Nm                |
| Power supply voltage  | DC 24 V ± 10 %         |
| Coil current          | 1.0 A                  |
| Opening time          | 300 ms                 |
| Closing time          | 70 ms                  |
| Highest braking work  | 3,380 J                |

### Recommended Motor Module

|                          |           |
|--------------------------|-----------|
| Rated inverter current   | 30 A      |
| Maximum inverter current | 72 A      |
| Maximum torque           | 150.00 Nm |