

## Data sheet for SIMOTICS S-1FL2

Article No. : 1FL2102-4AF10-0HC0



Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Basic motor data

Motor type	Permanent-magnet synchronous motor
Motor type	Low Inertia
Static torque	0.32 Nm
Static current	0.81 A
Maximum torque	1.12 Nm
Maximum current	2.90 A
Maximum speed	6,500 rpm
Rotor moment of inertia	0.0290 kgcm <sup>2</sup>
Weight	0.55 kg

### Rated data

SINAMICS S200, 3 AC 380 ... 480 V

Rated speed	3,000 rpm
Rated torque	0.32 Nm
Rated current	0.81 A
Rated power	0.10 kW

### Encoder system

Encoder system Absolute encoder singleturn 17 bit

### Motor connection

Connection type Metal hybrid connector

### Mechanical data

Design acc. to Code I	IM B5 (IM V1, IM V3)
Vibration severity grade	Grade A
Shaft height	20
Flange size (AB)	40.6 mm
Centering ring (N)	30 mm
Hole circle (M)	46 mm
Screw-on hole (S)	4.4 mm
Overall length (LB)	109.9 mm
Diameter of shaft (D)	8 mm
Length of shaft (E)	25 mm
Length of flange diagonal (P)	54 mm
Shaft end	Plain shaft
Color of the housing	Anthracite RAL 7016



### Holding brake

Rated voltage	24 V DC 10 %
Rated current	0.25 A
Holding torque $M_{4Br}$	0.32 Nm
Opening time	35 ms
Closing time	10 ms