

Data sheet for SIMOTICS S-1FL2

Article No. : 1FL2103-4AG01-1MC0



Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Basic motor data

| | |
|-------------------------|------------------------------------|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | Low Inertia |
| Static torque | 1.27 Nm |
| Static current | 2.40 A |
| Maximum torque | 4.45 Nm |
| Maximum current | 8.70 A |
| Maximum speed | 6,500 rpm |
| Rotor moment of inertia | 0.1550 kgcm ² |
| Weight | 1.16 kg |

Rated data

SINAMICS S200, 1/3 AC 200 ... 240 V

| | |
|---------------|-----------|
| Rated speed | 3,000 rpm |
| Rated torque | 1.27 Nm |
| Rated current | 2.40 A |
| Rated power | 0.40 kW |

Encoder system

| | |
|----------------|---|
| Encoder system | Absolute encoder 21-bit singleturn + 12-bit multiturn |
|----------------|---|

Motor connection

| | |
|-----------------|------------------------|
| Connection type | Metal hybrid connector |
|-----------------|------------------------|

Mechanical data

| | |
|-------------------------------|--|
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Vibration severity grade | Grade A |
| Shaft height | 30 |
| Flange size (AB) | 60.2 mm |
| Centering ring (N) | 50 mm |
| Hole circle (M) | 70 mm |
| Screw-on hole (S) | 5.4 mm |
| Overall length (LB) | 94.5 mm |
| Diameter of shaft (D) | 14 mm |
| Length of shaft (E) | 30 mm |
| Length of flange diagonal (P) | 81 mm |
| Shaft end | Shaft with parallel key (half-key balancing) |
| Color of the housing | Anthracite RAL 7016 |

