

## Data sheet for SIMOTICS S-1FL2

Article No. : 1FL2203-2AF11-1HC0



Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Basic motor data

|                         |                                    |
|-------------------------|------------------------------------|
| Motor type              | Permanent-magnet synchronous motor |
| Motor type              | Medium Inertia                     |
| Static torque           | 0.64 Nm                            |
| Static current          | 1.30 A                             |
| Maximum torque          | 2.24 Nm                            |
| Maximum current         | 4.80 A                             |
| Maximum speed           | 6,500 rpm                          |
| Rotor moment of inertia | 0.1800 kgcm <sup>2</sup>           |
| Weight                  | 1.12 kg                            |

### Rated data

SINAMICS S200, 3 AC 380 ... 480 V

|               |           |
|---------------|-----------|
| Rated speed   | 3,000 rpm |
| Rated torque  | 0.64 Nm   |
| Rated current | 1.30 A    |
| Rated power   | 0.20 kW   |

### Encoder system

Encoder system Absolute encoder singleturn 17 bit

### Motor connection

Connection type Metal hybrid connector

### Mechanical data

|                               |  |
|-------------------------------|--|
| Design acc. to Code I         | IM B5 (IM V1, IM V3)                         |
| Vibration severity grade      | Grade A                                      |
| Shaft height                  | 30   |
| Flange size (AB)              | 60.2 mm                                      |
| Centering ring (N)            | 50 mm  |
| Hole circle (M)               | 70 mm  |
| Screw-on hole (S)             | 5.4 mm                                       |
| Overall length (LB)           | 104 mm                                       |
| Diameter of shaft (D)         | 14 mm  |
| Length of shaft (E)           | 30 mm  |
| Length of flange diagonal (P) | 81 mm  |
| Shaft end                     | Shaft with parallel key (half-key balancing) |
| Color of the housing          | Anthracite RAL 7016                          |



### Holding brake

|                          |              |
|--------------------------|--------------|
| Rated voltage            | 24 V DC 10 % |
| Rated current            | 0.30 A       |
| Holding torque $M_{4Br}$ | 1.30 Nm      |
| Opening time             | 60 ms        |
| Closing time             | 10 ms        |