

## Data sheet for SIMOTICS M-1PH1

Article No. : 1PH1131-1HD12-1GA0



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated power	7.5 kW
Rated speed	1,000 rpm
Rated torque	71.6 Nm
Rated current	26.6 A
Rated voltage	220 V
Maximum speed	6,000 rpm
Maximum current	53.2 A
Power for duty type S6-25%, maximum	11.25 kW
Standstill torque for duty type S6-25%, maximum	107.0 Nm
Standstill current for duty type S6-25%, maximum	38.0 A
Field weakening speed, max.	5,000 rpm
Supply voltage, max.	355 V
Line frequency	35.2 Hz

### Ambient conditions

Ambient temperature	
Operation	-15 ... 40 °C
Storage	-20 ... 65 °C
Relative humidity	
Max. operation	90 %
Bearing, max.	95 %

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced-air cooling via fan
Vibration severity grade	Grade B
Degree of protection	IP54
Design acc. to Code I	IM B5 / IM V1
Color	Anthracite 614 / ~ RAL7016
Shaft end	Feather key with full key balancing
Sound pressure level (1m)	72 dB
Thermal class	F
Mounting type	Flange (round)
Encoder system	Absolute encoder single-turn (20 bit)