

## Data sheet for SIMOTICS M-1PH1

Article No. : 1PH1133-1LD10-2GA0



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated power	11.0 kW
Rated speed	1,000 rpm
Rated torque	105.0 Nm
Rated current	28.3 A
Rated voltage	301 V
Maximum speed	6,000 rpm
Maximum current	56.6 A
Power for duty type S6-25%, maximum	16.50 kW
Standstill torque for duty type S6-25%, maximum	158.0 Nm
Standstill current for duty type S6-25%, maximum	40.0 A
Field weakening speed, max.	3,000 rpm
Supply voltage, max.	355 V
Line frequency	35.0 Hz

### Ambient conditions

#### Ambient temperature

Operation	-15 ... 40 °C
Storage	-20 ... 65 °C

#### Relative humidity

Max. operation	90 %
Bearing, max.	95 %

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced-air cooling via fan
Vibration severity grade	Grade B
Degree of protection	IP54
Design acc. to Code I	IM B3 / IM V5
Color	Anthracite 614 / ~ RAL7016
Shaft end	Feather key with half key balancing
Sound pressure level (1m)	72 dB
Thermal class	F
Mounting type	Foot-mounted
Encoder system	Incremental encoder, TTL 2500 ppr (13 bit)