



SITOR fuse link, with slotted blade contacts, 2 x NH3L, In: 1400 A, aR, Un DC: 1250 V, front indicator

Figure similar

Model	
product brand name	SETRON
product designation	SITOR fuse link
design of the product	With slotted blade contacts
design of an identification indicator	front indicator
design of the switching contact	with slotted blade contacts for M10 screw fixing
design of the fuse link	Parallel SITOR semiconductor fuse, LV HRC design
General technical data	
size of fuse system according to EN 60269-1	2 x NH3L
operating class of the fuse link	aR
type of voltage of the operating voltage	DC
Supply voltage	
supply voltage	
• at DC	1 250 V
Breaking Capacity	
switching capacity current	
• at DC according to IEC 60947-2 rated value	150 kA
Dissipation	
power loss [W]	250 W
power loss [W]	
• for rated value of the current at AC in hot operating state per pole	250 W
• maximum	250 W
Product details	
product description	with bolt-on links, silver-plated
accessories included	no
Mechanical Design	
mounting position	Any, preferably vertical
Net Weight	3.898 kg
Environmental conditions	
ambient temperature during operation	
• minimum	-20 °C
• maximum	50 °C
environmental category	-20 to +50 at 95% relative humidity
Approvals Certificates	
General Product Approval	other



EG-Konf.



UR



[Confirmation](#)

## Environment

[Environmental Confirmations](#)

## Further information

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information for data generation and storage**

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NB2355-4KK16>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3NB2355-4KK16>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**


[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NB2355-4KK16](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NB2355-4KK16)

**CAx-Online-Generator**

<https://www.siemens.com/cax>

**Tender specifications**

<https://www.siemens.com/specifications>



last modified:

5/24/2025 

