



Connecting cable, 14-pole 8 mm

| General technical data | | |
|---|----|-----------------------------------|
| product brand name | | SIRIUS |
| product designation | | connecting cable, 14 poles |
| protection class IP on the front according to IEC 60529 | | IP20 |
| touch protection on the front according to IEC 60529 | | Finger-safe, for vertical contact |
| relative humidity during operation | % | 10 ... 90 |
| ambient temperature | | |
| • during transport | °C | -55 ... +80 |
| • during storage | °C | -55 ... +80 |
| • during operation | °C | -20 ... +60 |
| reference code according to EN 61346-2 | | W |
| Installation/ mounting/ dimensions | | |
| width | mm | 25 |
| Connections/ Terminals | | |
| wire length of connection cable | mm | 25 |
| Certificates/ approvals | | |
| certificate of suitability | | IEC / EN 60947-6-2 |
| General Product Approval | | EMV Maritime application |



| other | Environment |
|-------|-------------|
|-------|-------------|



[Confirmation](#)

[Environmental Con-
firmations](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
 Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
 Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
 Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA6931-0A>
 Cax online generator
<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA6931-0A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA6931-0A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA6931-0A&lang=en

last modified:

4/2/2025 