



contactor AC-1, 40 A, 400 V / 40 °C, 4-pole, 230 V AC, 50/60 Hz, auxiliary contacts: 1 NO + 1 NC, spring-loaded terminal, size: S0

|   |                            |
|---|----------------------------|
| <b>product brand name</b>   | SIRIUS                     |
| <b>product designation</b>  | Contactor                  |
| <b>product type designation</b>   | 3RT23                      |
| <b>General technical data</b>   |                            |
| <b>size of contactor</b>  | S0                         |
| <b>product extension</b>  |                            |
| • function module for communication   | No                         |
| • auxiliary switch  | Yes                        |
| <b>power loss [W] for rated value of the current</b>                          |                            |
| • at AC in hot operating state  | 9.6 W                      |
| • at AC in hot operating state per pole                                       | 2.4 W                      |
| • without load current share typical  | 2.6 W                      |
| <b>type of calculation of power loss depending on pole</b>                    | quadratic                  |
| <b>insulation voltage</b>   |                            |
| • of main circuit with degree of pollution 3 rated value                      | 690 V                      |
| • of the auxiliary and control circuit with degree of pollution 3 rated value | 690 V                      |
| <b>surge voltage resistance</b>   |                            |
| • of main circuit rated value   | 6 kV                       |
| • of auxiliary circuit rated value  | 6 kV                       |
| <b>shock resistance at rectangular impulse</b>                                |                            |
| • at AC   | 8,3g / 5 ms, 5,3g / 10 ms  |
| <b>shock resistance with sine pulse</b>                                       |                            |
| • at AC   | 13,5g / 5 ms, 8,3g / 10 ms |
| <b>mechanical service life (operating cycles)</b>                             |                            |
| • of contactor typical  | 10 000 000                 |
| • of the contactor with added auxiliary switch block typical                  | 10 000 000                 |
| <b>reference code according to IEC 81346-2</b>                                | Q                          |
| <b>Substance Prohibition (Date)</b>   | 10/01/2009                 |
| <b>Weight</b>   | 0.57 kg                    |
| <b>Ambient conditions</b>   |                            |
| installation altitude at height above sea level maximum                       | 2 000 m                    |
| <b>ambient temperature</b>  |                            |
| • during operation  | -25 ... +60 °C             |
| • during storage  | -55 ... +80 °C             |
| <b>relative humidity minimum</b>  | 10 %                       |
| <b>relative humidity at 55 °C according to IEC 60068-2-30 maximum</b>         | 95 %                       |
| <b>Environmental footprint</b>  |                            |
| Environmental Product Declaration (EPD)                                       | Yes                        |
| global warming potential [CO <sub>2</sub> eq] total                           | 166 kg                     |

|   |                                       |
|---|---------------------------------------|
| global warming potential [CO2 eq] during manufacturing  | 2.26 kg                               |
| global warming potential [CO2 eq] during operation  | 164 kg                                |
| global warming potential [CO2 eq] after end of life   | -0.152 kg                             |
| <b>Main circuit</b>   |                                       |
| <b>number of poles for main current circuit</b>   | 4                                     |
| <b>number of NO contacts for main contacts</b>  | 4                                     |
| <b>type of voltage for main current circuit</b>   | AC                                    |
| <b>operational current</b>  |                                       |
| <ul style="list-style-type: none"> <li>● at AC-1 at 400 V at ambient temperature 40 °C rated value</li> </ul>   | 40 A                                  |
| <ul style="list-style-type: none"> <li>● at AC-1 <ul style="list-style-type: none"> <li>— up to 690 V at ambient temperature 40 °C rated value</li> <li>— up to 690 V at ambient temperature 60 °C rated value</li> </ul> </li> </ul>   | 40 A<br>35 A                          |
| <ul style="list-style-type: none"> <li>● at AC-3 <ul style="list-style-type: none"> <li>— at 400 V rated value</li> </ul> </li> </ul>   | 15.5 A                                |
| <ul style="list-style-type: none"> <li>● at AC-4 at 400 V rated value</li> </ul>  | 15.5 A                                |
| minimum cross-section in main circuit at maximum AC-1 rated value   | 10 mm <sup>2</sup>                    |
| <b>operational current</b>  |                                       |
| <ul style="list-style-type: none"> <li>● <b>at 1 current path at DC-1</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> </ul> </li> </ul>                      | 35 A<br>20 A<br>4.5 A<br>1 A<br>0.4 A |
| <ul style="list-style-type: none"> <li>● <b>with 2 current paths in series at DC-1</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> </ul> </li> </ul>         | 35 A<br>35 A<br>35 A<br>1 A<br>1 A    |
| <ul style="list-style-type: none"> <li>● <b>with 3 current paths in series at DC-1</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> </ul> </li> </ul>         | 35 A<br>35 A<br>35 A<br>35 A<br>2.9 A |
| <ul style="list-style-type: none"> <li>● <b>at 1 current path at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> </ul> </li> </ul>              | 20 A<br>5 A<br>2.5 A<br>1 A<br>0.09 A |
| <ul style="list-style-type: none"> <li>● <b>with 2 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> </ul> </li> </ul> | 35 A<br>35 A<br>15 A<br>3 A<br>0.27 A |
| <ul style="list-style-type: none"> <li>● <b>with 3 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> </ul> </li> </ul> | 35 A<br>35 A<br>35 A<br>10 A<br>0.6 A |
| <b>operating power</b>  |                                       |
| <ul style="list-style-type: none"> <li>● at AC-3 at 400 V rated value</li> <li>● at AC-4 at 400 V rated value</li> </ul>  | 7.5 kW<br>7.5 kW                      |
| <b>no-load switching frequency</b>  |                                       |
| <ul style="list-style-type: none"> <li>● at AC</li> </ul>   | 5 000 1/h                             |

|   |   |
|---|---|
| operating frequency at AC-1 maximum   | 1 000 1/h                                       |
| <b>Control circuit/ Control</b>   |   |
| <b>type of voltage</b>  | AC  |
| <b>type of voltage of the control supply voltage</b>                                  | AC  |
| <b>control supply voltage at AC</b>   |   |
| • at 50 Hz rated value  | 230 V   |
| • at 60 Hz rated value  | 230 V   |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b> |   |
| • at 50 Hz  | 0.8 ... 1.1                                     |
| • at 60 Hz  | 0.85 ... 1.1                                    |
| <b>apparent pick-up power of magnet coil at AC</b>                                    |   |
| • at 50 Hz  | 81 VA   |
| • at 60 Hz  | 79 VA   |
| <b>inductive power factor with closing power of the coil</b>                          |   |
| • at 50 Hz  | 0.72  |
| • at 60 Hz  | 0.74  |
| <b>apparent holding power of magnet coil at AC</b>                                    |   |
| • at 50 Hz  | 10.5 VA   |
| • at 60 Hz  | 8.5 VA  |
| <b>inductive power factor with the holding power of the coil</b>                      |   |
| • at 50 Hz  | 0.25  |
| • at 60 Hz  | 0.28  |
| <b>closing delay</b>  |   |
| • at AC   | 8 ... 40 ms                                     |
| <b>opening delay</b>  |   |
| • at AC   | 4 ... 16 ms                                     |
| <b>arcing time</b>  | 10 ... 10 ms                                    |
| <b>control version of the switch operating mechanism</b>                              | Standard A1 - A2                                |
| <b>Auxiliary circuit</b>  |   |
| <b>number of NC contacts for auxiliary contacts</b>                                   | 1   |
| • attachable  | 2   |
| • instantaneous contact   | 1   |
| <b>number of NO contacts for auxiliary contacts</b>                                   | 1   |
| • attachable  | 2   |
| • instantaneous contact   | 1   |
| operational current at AC-12 maximum  | 10 A  |
| <b>operational current at AC-15</b>   |   |
| • at 230 V rated value  | 10 A  |
| • at 400 V rated value  | 3 A   |
| • at 500 V rated value  | 2 A   |
| • at 690 V rated value  | 1 A   |
| <b>operational current at DC-12</b>   |   |
| • at 24 V rated value   | 10 A  |
| • at 48 V rated value   | 6 A   |
| • at 60 V rated value   | 6 A   |
| • at 110 V rated value  | 3 A   |
| • at 125 V rated value  | 2 A   |
| • at 220 V rated value  | 1 A   |
| • at 600 V rated value  | 0.15 A  |
| <b>operational current at DC-13</b>   |   |
| • at 24 V rated value   | 10 A  |
| • at 48 V rated value   | 2 A   |
| • at 110 V rated value  | 1 A   |
| • at 125 V rated value  | 0.9 A   |
| • at 220 V rated value  | 0.3 A   |
| • at 600 V rated value  | 0.1 A   |
| <b>contact reliability of auxiliary contacts</b>                                      | 1 faulty switching per 100 million (17 V, 1 mA) |
| <b>UL/CSA ratings</b>   |   |
| <b>contact rating of auxiliary contacts according to UL</b>                           | A600 / Q600                                     |
| <b>Category Control Number (CCN)</b>  | E31519 (NLDX, NLDX7)                            |

| Short-circuit protection  |   |
|---|---|
| design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V   | C characteristic: 10 A; 0.4 kA  |
| <b>design of the fuse link</b> <ul style="list-style-type: none"> <li>• for short-circuit protection of the main circuit <ul style="list-style-type: none"> <li>— with type of coordination 1 required</li> <li>— with type of coordination 2 required</li> </ul> </li> <li>• for short-circuit protection of the auxiliary switch required</li> </ul>  | gG: 63 A (690 V, 100 kA)<br>gG: 20 A (690 V, 100 kA)<br>gG: 10 A (690 V, 1 kA)  |
| Installation/ mounting/ dimensions  |   |
| <b>mounting position</b>  | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface                |
| fastening method side-by-side mounting  | Yes   |
| <b>fastening method</b>   | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715  |
| <b>height</b>   | 102 mm  |
| <b>width</b>  | 60 mm   |
| <b>depth</b>  | 97 mm   |
| <b>required spacing</b> <ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— at the side</li> <li>— downwards</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> </ul> | 10 mm<br>10 mm<br>10 mm<br>0 mm<br><br>10 mm<br>10 mm<br>6 mm<br>10 mm<br><br>10 mm<br>10 mm<br>10 mm<br>6 mm                                       |
| Connections/ Terminals  |   |
| <b>type of electrical connection</b> <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for auxiliary and control circuit</li> <li>• at contactor for auxiliary contacts</li> <li>• of magnet coil</li> </ul>   | spring-loaded terminals<br>spring-loaded terminals<br>Spring-type terminals<br>Spring-type terminals  |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid</li> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> <li>— finely stranded without core end processing</li> </ul> </li> <li>• for AWG cables for main contacts</li> </ul>  | 2x (1 ... 10 mm <sup>2</sup> )<br>2x (1 ... 10 mm <sup>2</sup> )<br>2x (1 ... 6 mm <sup>2</sup> )<br>2x (1 ... 6 mm <sup>2</sup> )<br>2x (18 ... 8) |
| <b>connectable conductor cross-section for main contacts</b> <ul style="list-style-type: none"> <li>• solid</li> <li>• solid or stranded</li> <li>• stranded</li> <li>• finely stranded with core end processing</li> <li>• finely stranded without core end processing</li> </ul>  | 1 ... 10 mm <sup>2</sup><br>1 ... 10 mm <sup>2</sup><br>1 ... 10 mm <sup>2</sup><br>1 ... 6 mm <sup>2</sup><br>1 ... 6 mm <sup>2</sup>              |
| <b>connectable conductor cross-section for auxiliary contacts</b> <ul style="list-style-type: none"> <li>• solid or stranded</li> <li>• finely stranded with core end processing</li> <li>• finely stranded without core end processing</li> </ul>  | 0.5 ... 2.5 mm <sup>2</sup><br>0.5 ... 1.5 mm <sup>2</sup><br>0.5 ... 2.5 mm <sup>2</sup>   |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid</li> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> <li>— finely stranded without core end processing</li> </ul> </li> </ul>   | 2x (0.5 ... 2.5 mm <sup>2</sup> )<br>2x (0.5 ... 2.5 mm <sup>2</sup> )<br>2x (0.5 ... 1.5 mm <sup>2</sup> )<br>2x (0.5 ... 2.5 mm <sup>2</sup> )    |

|   |                |
|---|----------------|
| • for AWG cables for auxiliary contacts   | 2x (20 ... 14) |
| <b>AWG number as coded connectable conductor cross section for main contacts</b>      | 18 ... 8       |
| <b>AWG number as coded connectable conductor cross section for auxiliary contacts</b> | 20 ... 14      |

### Safety related data

|  |     |
|--|-----|
| <b>product function</b>                                  |     |
| • mirror contact according to IEC 60947-4-1              | Yes |
| • positively driven operation according to IEC 60947-5-1 | No  |

### Electrical Safety

|  |  |
|--|--|
| <b>protection class IP on the front according to IEC 60529</b> | IP20   |
| <b>touch protection on the front according to IEC 60529</b>    | finger-safe, for vertical contact from the front |

### Communication/ Protocol

|   |    |
|---|----|
| <b>product function bus communication</b> | No |
|---|----|

### Approvals Certificates

|                                 |     |
|---------------------------------|-----|
| <b>General Product Approval</b> | EMV |
|---------------------------------|-----|



### Test Certificates

|  |  |  |  |  |  |
|--|--|--|--|--|--|
| <a href="#">Type Test Certificates/Test Report</a> | <a href="#">Special Test Certificate</a> |  |  |  |  |
|--|--|--|--|--|--|

### Maritime application

|  |  |  |                               |  |                              |
|--|--|--|-------------------------------|--|------------------------------|
|  |  |  | <a href="#">Miscellaneous</a> |  | <a href="#">Confirmation</a> |
|--|--|--|-------------------------------|--|------------------------------|

### Railway

|  |  |   |
|--|--|---|
| <a href="#">Special Test Certificate</a> |  | <a href="#">Environmental Confirmations</a> |
|--|--|---|

### Further information

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>  
 Information for data generation and storage  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>  
 Information- and Downloadcenter (Catalogs, Brochures,...)  
<https://www.siemens.com/ic10>  
 Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2326-2AL20>  
 Cax online generator  
<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2326-2AL20>  
 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/3RT2326-2AL20>  
 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)  
[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2326-2AL20&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2326-2AL20&lang=en)  
 Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current  
<https://support.industry.siemens.com/cs/ww/en/ps/3RT2326-2AL20/char>  
 Further characteristics (e.g. electrical endurance, switching frequency)  
<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2326-2AL20&objecttype=14&gridview=view1>





last modified:

11/14/2025 