



lower part of enclosure for 3RW50 frame size S6

|                                               |                        |
|-----------------------------------------------|------------------------|
| product designation                           | Enclosure lower part   |
| product type designation                      | 3RW59                  |
| manufacturer's article number of soft starter | <a href="#">3RW505</a> |

General technical data

|                                |            |
|--------------------------------|------------|
| Substance Prohibittance (Date) | 09/23/2019 |
| Weight                         | 0.395 kg   |

Ambient conditions

|                                    |                |
|------------------------------------|----------------|
| ambient temperature during storage | -40 ... +80 °C |
|------------------------------------|----------------|

Approvals Certificates

|                          |     |                                 |                   |
|--------------------------|-----|---------------------------------|-------------------|
| General Product Approval | EMV | For use in hazard-ous locations | Test Certificates |
|--------------------------|-----|---------------------------------|-------------------|



[KC](#)

[Miscellaneous](#)

[Type Test Certificates/Test Report](#)

|                      |       |
|----------------------|-------|
| Maritime application | other |
|----------------------|-------|



[Confirmation](#)

Environment

[Environmental Con-  
firmations](#)

Further information

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>  
Information for data generation and storage  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>  
Information- and Downloadcenter (Catalogs, Brochures,...)  
<https://www.siemens.com/ic10>  
Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5905-0GB00>  
Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5905-0GB00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5905-0GB00>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5905-0GB00&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5905-0GB00&lang=en)

**Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5905-0GB00/char>

**Characteristic: Installation altitude**

<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5905-0GB00&objecttype=14&gridview=view1>

**Simulation Tool for Soft Starters (STS)**

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

---

last modified:

4/17/2025 

