



Control unit 24 V for 3RW52, Size 1 to 4 Analog output

|   |                             |
|---|-----------------------------|
| product designation                           | Control unit                |
| design of the product                         | 24 V, analog output         |
| product type designation                      | 3RW59                       |
| manufacturer's article number of soft starter | <a href="#">3RW52...AC0</a> |

| General technical data         |  |
|--------------------------------|--|
| Substance Prohibittance (Date) | 02/15/2018   |
| SVHC substance name            | Lead - 7439-92-1<br>Lead monoxide (lead oxide) - 1317-36-8<br>6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol - 119-47-1<br>2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one - 71868-10-5 |
| Weight                         | 0.68 kg  |

| Ambient conditions                 |                |
|------------------------------------|----------------|
| ambient temperature during storage | -40 ... +80 °C |

| Approvals Certificates   |     |                                |                   |
|--------------------------|-----|--------------------------------|-------------------|
| General Product Approval | EMV | For use in hazardous locations | Test Certificates |



[KC](#)

[Miscellaneous](#)

[Type Test Certificates/Test Report](#)

| Maritime application | other |
|----------------------|-------|
|----------------------|-------|



[Confirmation](#)



| Environment                                 |
|---|
| <a href="#">Environmental Conformations</a> |

### Further information

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>  
 Information for data generation and storage  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5920-1UA00>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5920-1UA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5920-1UA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5920-1UA00&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5920-1UA00&lang=en)

Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5920-1UA00/char>

Characteristic: Installation altitude

<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5920-1UA00&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

---

last modified:

4/2/2025 

