

Siemens  
EcoTech



Indicator lights, 22 mm, round, metal, shiny, white, lens, smooth



|                                                          |                                                                    |
|----------------------------------------------------------|--------------------------------------------------------------------|
| product brand name                                       | SIRIUS ACT                                                         |
| product designation                                      | Indicator lights                                                   |
| design of the product                                    | Actuating/signaling element                                        |
| product type designation                                 | 3SU1                                                               |
| product line                                             | Metal, shiny, 22 mm                                                |
| <b>Actuator</b>                                          |                                                                    |
| product extension optional                               |                                                                    |
| • light source                                           | Yes                                                                |
| • contact module                                         | No                                                                 |
| color                                                    |                                                                    |
| • of the actuating element                               | white                                                              |
| • of the cover cap                                       | white                                                              |
| material of the actuating element                        | plastic                                                            |
| shape of the actuating element                           | round                                                              |
| outer diameter of the actuating element                  | 29.45 mm                                                           |
| <b>Front ring</b>                                        |                                                                    |
| product component front ring                             | No                                                                 |
| material of the front ring                               | plastic                                                            |
| color of the front ring                                  | black                                                              |
| <b>General technical data</b>                            |                                                                    |
| protection class IP                                      | IP66, IP67, IP69(IP69K)                                            |
| degree of protection NEMA rating                         | 1, 2, 3, 3R, 4, 4X, 12, 13                                         |
| shock resistance                                         |                                                                    |
| • according to IEC 60068-2-27                            | sinusoidal half-wave 15g / 11 ms                                   |
| vibration resistance                                     |                                                                    |
| • according to IEC 60068-2-6                             | 10 ... 500 Hz: 5g                                                  |
| reference code according to IEC 81346-2                  | P                                                                  |
| Substance Prohibitance (Date)                            | 10/01/2014                                                         |
| Weight                                                   | 26 g                                                               |
| <b>Connections/ Terminals</b>                            |                                                                    |
| tightening torque of the screws in the bracket           | 1 ... 1.2 N·m                                                      |
| <b>Ambient conditions</b>                                |                                                                    |
| ambient temperature                                      |                                                                    |
| • during operation                                       | -25 ... +70 °C                                                     |
| • during storage                                         | -40 ... +80 °C                                                     |
| environmental category during operation according to IEC | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |

|       |  |
|-------|--|
| 60721 |  |
|-------|--|

## Environmental footprint

|                                                        |                 |
|--------------------------------------------------------|-----------------|
| Environmental Product Declaration(EPD)                 | Yes             |
| global warming potential [CO2 eq] total                | 0.593 kg        |
| global warming potential [CO2 eq] during manufacturing | 0.625 kg        |
| global warming potential [CO2 eq] during operation     | 0.235 kg        |
| global warming potential [CO2 eq] after end of life    | -0.267 kg       |
| Siemens Eco Profile (SEP)                              | Siemens EcoTech |

## Installation/ mounting/ dimensions

|                                             |         |
|---------------------------------------------|---------|
| height                                      | 29.5 mm |
| width                                       | 29.5 mm |
| shape of the installation opening           | round   |
| mounting diameter                           | 22.3 mm |
| positive tolerance of installation diameter | 0.4 mm  |
| mounting height                             | 11.8 mm |
| installation width                          | 29.5 mm |
| installation depth                          | 24.4 mm |

## Approvals Certificates

|                          |                   |                      |
|--------------------------|-------------------|----------------------|
| General Product Approval | Test Certificates | Maritime application |
|--------------------------|-------------------|----------------------|



[Type Test Certificates/Test Report](#)



|                      |       |             |
|----------------------|-------|-------------|
| Maritime application | other | Environment |
|----------------------|-------|-------------|



[Confirmation](#)



## Environment



[Environmental Confirmations](#)

## Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1051-6AA60-0AA0>

Cax online generator


<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1051-6AA60-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1051-6AA60-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1051-6AA60-0AA0&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1051-6AA60-0AA0&lang=en)



---

last modified:

11/15/2025 