



Memory module for the parameterization of SIMOCODE pro S/V without PC/PG, Color: titanium gray

General technical data

product designation	memory module
ambient temperature	
<ul style="list-style-type: none"> during storage 	-40 ... +80 °C
<ul style="list-style-type: none"> during operation 	-25 ... +60 °C
<ul style="list-style-type: none"> during transport 	-40 ... +80 °C

Certificates/ approvals

General Product Approval	EMV	Test Certificates
 EG-Konf.		
	 RCM	KC
		Type Test Certificates/Test Report

Maritime application	other	Environment	Industrial Communication
 ABS	 RMRS	 产品合格 QC PASS	Confirmation
		Environmental Confirmations	 Profibus

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7901-0AA01-0>
- Cax online generator
<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7901-0AA01-0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3UF7901-0AA01-0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7901-0AA01-0&lang=en





