



Figure similar

\*\*\*spare part\*\*\* SIPLUS S7-300 PS 307 10 A based on 6ES7307-1KA02-0AA0 with conformal coating, -25...+70 °C, stabilized power supply PS 307 input: 120/230 V AC output: 24 V DC/10 A

General information	
based on	<a href="#">6ES7307-1KA02-0AA0</a>
Supply voltage	
Rated value (AC)	
• 120 V AC	Yes; 85 to 132 V AC
• 230 V AC	Yes; 170 to 264 V AC
Oversvoltage strength	2.3x U <sub>e</sub> rated, 1.3 ms
Line frequency	
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Mains buffering	
• Mains/voltage failure stored energy time	20 ms; min., for I <sub>a</sub> rated and U <sub>e</sub> = 93 / 187 V
• Repeat rate, min.	1 s
Input current	
Rated value at 120 V AC	4.2 A
Rated value at 230 V AC	1.9 A
Inrush current, max.	55 A; max. at 25 °C, duration max. 3 ms
I <sup>2</sup> t	3.3 A <sup>2</sup> ·s
Leakage current, typ.	0.6 mA
Leakage current, max.	3.5 mA
Overcurrent overload capability	80 ms on short circuit during startup and operation
output voltage / header	
Rated value (DC)	24 V; stable at no-load max. 2.5 s
permissible range, lower limit (DC)	23.27 V
permissible range, upper limit (DC)	24.72 V
Power up time, max.	2 s
Voltage rise time, typ.	10 ms
Oversvoltage protection	Additional control circuit, cutoff at < 28.8 V, automatic restart
Short-circuit protection	electronic trip, automatic restart
Residual ripple, typ.	15 mV; Peak - peak
Residual ripple, max.	50 mV; Peak - peak
Output current	
Current output (rated value)	10 A; 7 A @ > 60 °C, can be switched in parallel
Short-circuit protection	Yes; Electronic
Continuous short-circuit current, max.	12 A
Power	
Active power input, typ.	267 W
Efficiency	90 %; approx., at U <sub>a</sub> rated, I <sub>a</sub> rated

<b>Power loss</b>	
Power loss, typ.	27 W; approx., at U <sub>a</sub> rated, I <sub>a</sub> rated
<b>Interrupts/diagnostics/status information</b>	
Diagnostics indication LED	
• Status indicator output 24 V OK (green)	Yes
<b>Potential separation</b>	
primary/secondary	Yes; SELV output voltage U <sub>a</sub> according to EN 60950-1 and EN 50178
<b>Isolation</b>	
Isolation tested with	Rated insulation voltage (24 V against L1) 250 V AC, tested with 4 200 V DC
<b>EMC</b>	
EMC interference immunity	EN 61000-6-2
EMC interference emission	EN 55022 Class B
<b>Degree and class of protection</b>	
Equipment protection class	I, with protective conductor
<b>Standards, approvals, certificates</b>	
CE mark	Yes
Standard for line harmonics limit	EN 61000-3-2
<b>Ambient conditions</b>	
Ambient temperature during operation	
• min.	-25 °C; = T <sub>min</sub>
• max.	70 °C; = T <sub>max</sub> ; 60 °C @ UL/cUL, ATEX and FM use
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
• Ambient air temperature-barometric pressure-altitude	T <sub>min</sub> ... T <sub>max</sub> at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // T <sub>min</sub> ... (T <sub>max</sub> - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // T <sub>min</sub> ... (T <sub>max</sub> - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m); above 2 000 m max. 75 V DC
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
<b>Resistance</b>	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
<b>Dimensions</b>	
Width	80 mm
Height	125 mm
Depth	120 mm
<b>Weights</b>	
Weight, approx.	0.8 kg
<b>Classifications</b>	
	Version
	Classification

eClass	14	27-24-22-09
eClass	12	27-24-22-09
eClass	9.1	27-24-22-09
eClass	9	27-24-22-09
eClass	8	27-24-22-09
eClass	7.1	27-24-22-09
eClass	6	27-24-22-09
ETIM	10	EC000599
ETIM	9	EC000599
ETIM	8	EC000599
ETIM	7	EC000599
IDEA	4	3575
UNSPSC	15	32-15-17-06

**Approvals / Certificates**

General Product Approval	EMV
--------------------------	-----

[Manufacturer Declaration](#)



[China RoHS](#)



[KC](#)

EMV	For use in hazardous locations
-----	--------------------------------



[CCC-Ex](#)



last modified:

7/1/2025