


plug, female, 12-pole, 180°, max.: 1.5 mm², scope of supply: 10 plugs



General information	
Product type designation	Connector, female, 12-pin
Installation type/mounting	
Mounting type	Conductor cross-section 0.14 to 1.5 mm ²
Wall mounting/direct mounting	Yes; can be plugged into SIMATIC HMI device
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption (rated value)	9 A; Typical, maximum value
Interfaces	
HMI-side interface	
• Number of pins HMI-side	12; Female, spring-loaded terminals, 3.5 mm grid
Device-side interface	
• Number of pins device-side	12; Female, spring-loaded terminals
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes; 200039-1121690
UL approval	Yes; E60693
cULus	Yes; cURus
EAC (formerly Gost-R)	Yes
RoHS conformity	Yes
Use in hazardous areas	
• ATEX Zone 2	Yes; Device-dependent, see operating instructions
• ATEX Zone 22	Yes; Device-dependent, see operating instructions
• IECEx Zone 2	Yes; Device-dependent, see operating instructions
• IECEx Zone 22	Yes; Device-dependent, see operating instructions
• cULus Class I Zone 1	Yes; Device-dependent, see operating instructions
• cULus Class I Zone 2, Division 2	Yes; Device-dependent, see operating instructions
• FM Class I Division 2	Yes; Device-dependent, see operating instructions
Marine approval	
• Germanischer Lloyd (GL)	Yes; Always comply with the operating instructions of the target device.
• American Bureau of Shipping (ABS)	Yes; Always comply with the operating instructions of the target device.
• Bureau Veritas (BV)	Yes; Always comply with the operating instructions of the target device.
• Det Norske Veritas (DNV)	Yes; Always comply with the operating instructions of the target device.
• Korean Register of Shipping (KRS)	Yes; Always comply with the operating instructions of the target device.
• Lloyds Register of Shipping (LRS)	Yes; Always comply with the operating instructions of the target device.
• Nippon Kaiji Kyokai (Class NK)	Yes; Always comply with the operating instructions of the target device.
• Polski Rejestr Statkow (PRS)	Yes; Always comply with the operating instructions of the target device.
• Chinese Classification Society (CCS)	Yes; Always comply with the operating instructions of the target device.

Ambient conditions	
Suited for indoor use	Yes; Flammability class according to UL 94-V0
Suited for outdoor use	Yes; possible under certain conditions
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Relative humidity	
• Operation, max.	80 %
Mechanics/material	
Material	
• Plastic	Yes; Insulating material PA66 GF30, actuators PA66/6
Enclosure material (front)	
• Plastic	Yes; Spring-loaded terminals 1.5 mm ²
Enclosure color (front)	Black
Service life	
• Mechanical service life (mating cycles)	25
Dimensions	
Width	21 mm; 12-pin connector
Height	15.2 mm
Depth	26.25 mm
Weights	
Weight, approx.	7.9 g
Scope of supply	
Delivery quantity in pieces	10; Without ejector
Other	
Merchandise	Yes
Manufacturer name	Weidmüller Interface GmbH & Co. KG
Manufacturer's address	Klingenbergstraße 16, 32758 Detmold, Germany
Target devices	for KP8 PN

Classifications			
		Version	Classification
	eClass	14	27-33-02-92
	eClass	12	27-33-02-92
	eClass	9.1	27-33-02-92
	eClass	9	27-33-02-92
	eClass	8	27-24-92-03
	eClass	7.1	27-24-92-03
	eClass	6	27-24-92-03
	ETIM	10	EC002584
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03

Approvals / Certificates	
General Product Approval	EMV



Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415
<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified:

5/22/2024 