



SIMATIC IFP1200 Basic Flat Panel 12" display (16:10), Touch, 1280 x 800 pixels, standard up to 5 m, for 24V DC, DisplayPort/VGA interface

General information	
Product type designation	IFP1200 Basic
Short designation	Basic Flat Panel 12" Touch
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	12.1 in; 12"
On Screen Display (OSD) configuration	No
Number of colors	16 000 000; 16 million
Resolution (pixels)	
• Image resolution	1 280 x 800
• Horizontal image resolution	1 280 pixel
• Vertical image resolution	800 pixel
General features	
• Detachable from computer unit	5 m
Backlighting	
• Type of backlighting	LED
• MTBF backlighting (at 25 °C)	50 000 h
• Backlight dimmable	Yes; 0-100 %
Control elements	
Control elements	single-touch screen
Input device	
• Integrated mouse cursor control	No
Touch operation	
• Design as touch screen	Yes; Analog-resistive
Installation type/mounting	
Design	Built-in unit
Front mounting	Yes
VESA mounting	Yes; VESA 100 x 100 integrated
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Built-in unit	Yes; Portrait mode possible
maximum permitted forward tilt angle from vertical	45°
maximum permitted backward tilt angle from vertical	45°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Power loss	
Power loss, typ.	13 W

Power loss, max.	60 W	
Interfaces		
Number of USB interfaces	2; USB 2.0 (downstream)	
USB on the rear	Yes; 2x onboard	
Video interfaces		
• DisplayPort	Yes	
Touch interfaces		
• USB	Yes; USB 2.0 Type B	
Degree and class of protection		
IP (at the front)	IP65	
Standards, approvals, certificates		
CE mark	Yes	
cULus	Yes; UL 61010-1, UL 61010-2-201	
RCM (formerly C-TICK)	Yes	
KC approval	Yes	
EAC (formerly Gost-R)	Yes	
FCC	Yes	
Ambient conditions		
Ambient temperature during operation		
• min.	0 °C	
• max.	45 °C	
Ambient temperature during storage/transportation		
• min.	-20 °C	
• max.	60 °C	
Relative humidity		
• Operation, max.	85 %	
Vibrations		
• Vibration load in operation	5 m/s ²	
• Vibration load during transport/storage	10 m/s ²	
Shock testing		
• Shock load during operation	150 m/s ²	
• shock acceleration during storage/transport	150 m/s ²	
Mechanics/material		
Enclosure material (front)		
• Aluminum	Yes	
Dimensions		
Width of the housing front	319.6 mm	
Height of housing front	225.6 mm	
Mounting cutout, width	302 mm	
Mounting cutout, height	208 mm	
Overall depth	50.1 mm	
Weights		
Weight (without packaging)	2.7 kg	
Classifications		
	Version	Classification
eClass	14	19-20-02-01
eClass	12	19-20-02-01
eClass	9.1	19-20-02-01
eClass	9	19-20-02-01
eClass	8	19-20-02-01
eClass	7.1	19-20-02-01
eClass	6	19-20-02-01
ETIM	10	EC004862
ETIM	9	EC001428
ETIM	8	EC001428
ETIM	7	EC001428
IDEA	4	6675

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)[KC](#)

General Product Approval

EMV

[BIS_CRS](#)

last modified:

4/10/2024